# AS6

## AS6 IR TRANSMITTER

## Features

Simultaneous interpretation system for up to 6 languages with transmission via IR radiators. Allows connection of up to 6 translation desks. High sound quality without interference with lighting systems.




## Technical Specifications

| Feature | Specification |
|---|---|
| **Features:** | AS6 simultaneous interpretation system transmitter.<br>Up to 6 languages besides the original language.<br>Up to 10 AS-61M or AS-62M microphones can be connected in cascade.<br>Automatic control of output volume. |
| **Response:** | 100 – 16,000 Hz |
| **Inputs:** | |
| **Output Level in Each Channel:** | 6 lines, RCA 18,000 Ω 2 V<br>6 lines, RCA 600 Ω 1 V |
| **Outputs** | |
| **Radiators:** | 2 radiators, BNC 50 Ω |
| **Interpretation Units:** | 2 × DB25 |
| **S / N Ratio:** | >75 dB |
| **Power Supply:** | 110–240 V AC, 40 W |
| **Dimensions:** | 483 × 89 × 355 mm (depth) |
| **Weight:** | 7 kg |
| **Accessories:** | 10 m interconnection cable for interpretation units, DB25<br>2 × audio cables, 6.3 mm mono jack to RCA |



71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk