CS82Q

8" COAXIAL IN-CEILING SPEAKER

Features

- 8" coaxial in-ceiling speaker
- 8" woofer and a 1" coaxial compression driver
- Multi-tap transformer 70V/100V
- Included bridge rail installation kit
- White-painted magnetic grill coupled with a sturdy steel backcan



Technical Specifications

Feature	Specification
Frequency Response	65 Hz - 20 kHz
Sensitivity	93 dB
SPL Max	113 dB
Dispersion (H x V)	120° Conical
Configuration	8" coaxial in-ceiling speaker
Transducer	LF: 8", HF: 1" coaxial compression driver
Impedance	8 Ω
Power Handling (passive)	80/160W
70V	60/30/15/7.5W
100V	NC/60/30/15W
Connectors	4 pole euroblock connector
Cabinet Construction	Zinc plated steel
Mounting	Bridge rail installation kit
Finish	White painted grille
Grill	Powder coated steel grille with safety clip
Control	70V/100V/8-ohm tap switch
Dimensions (mm / Inch)	Φ 290 × 198.9 H / Φ 11.4 × 7.8 H
Weight	3.65 kg / 8 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk