CS43T

4 × 3" • 2 × 1.2" COLUMN ARRAY SPEAKER

Features

- 4 × 3" column speaker
- Aluminum enclosure
- 4 × 3" woofers, 2 × 1.2" soft dome tweeters
- IP-55 rated waterproof
- Included wall mount
- Both Speakon and EUROBLOCK connectors



Technical Specifications

Feature	Specification
Frequency Response:	102 Hz – 20 kHz
Sensitivity	102 dB, 1W @ 1m
Spl Max:	123 dB (Peak)
Dispersion (H × V):	140° × 25° (H × V)
Loudspeaker Data:	
Configuration:	4 × 3" passive column array speaker
Transducer:	LF: 4 × 3", HF: 2 × 1.2" dome tweeters
Impedance:	8 Ω
Power Handling:	120W / 240W
70v:	30W / 15W / 7.5W / 3.75W
100v:	30W / 15W / 7.5W
Connectors:	Speakon & EUROBLOCK connectors w/ waterproof cover
Physical:	
Cabinet Construction:	Extrusion aluminum
Mounting:	Wall-mount bracket or pole-mount adapter
Finish:	Black paint
Grill:	Aluminum with anti-corrosion coat
Dimensions (mm / Inch):	111 W – 98 D – 588 H / 4.4 W – 3.9 D – 23.2 H
Weight:	5 Kg / 11 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk