CS62Q

6.5" COAXIAL IN-CEILING SPEAKER



Features

- 6.5" coaxial in-ceiling speaker
- 6.5" woofer and a 1" coaxial compression driver
- Multi-tap transformer 70V/100V
- Included bridge rail installation kit
- White-painted magnetic grill coupled with a sturdy steel backcan

Technical Specifications

Feature	Specification
Frequency Response	70 Hz - 20 kHz
Sensitivity	91 dB
SPL Max	109 dB
Dispersion (H x V)	120° Conical
Configuration	6.5" coaxial in-ceiling speaker
Transducer	LF: 6.5", HF: 1" coaxial compression driver
Impedance	8 Ω
Power Handling (passive)	60/120W
70V	30/15/7.5/3.75W
100V	NC/30/15/7.5W
Connectors	4 pole euroblock connector
Cabinet Construction	Zinc plated steel
Mounting	Bridge rail installation kit
Finish	White painted
Grill	Powder coated steel grille with safety clip
Control	70V/100V/8-ohm tap switch
Dimensions (mm / Inch)	Φ 253 × 168.9 H / Φ 10 × 6.6 H
Weight	3.06 kg / 6.7 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk