CS63T

6 × 3" + 4 × 1.2" COLUMN ARRAY SPEAKER

Features

- 6 × 3" column speaker
- Aluminum enclosure
- 6 × 3" woofers, 4 × 1.2" soft dome tweeters
- IP-55 rated waterproof
- Included wall mount
- Both Speakon and EUROBLOCK connectors



Technical Specifications

Feature	Specification
Frequency Response:	100 Hz – 20 kHz
Sensitivity	102 dB, 1W @ 1m
Spl Max:	125 dB (Peak)
Dispersion (H × V):	140° × 25° (H × V)
Loudspeaker Data:	
Configuration:	6 × 3" passive column array speaker
Transducer:	LF: 6 × 3", HF: 4 × 1.2" dome tweeters
Impedance:	8 Ω
Power Handling:	200W / 400W
70v:	60 W / 30 W / 15 W / 7.5 W
100v:	60 W / 30 W / 15 W
Connectors:	Speakon & EUROBLOCK connectors w/ waterproof cover
Physical:	
Cabinet Construction:	Extrusion aluminum
Mounting:	Wall-mount bracket or pole-mount adapter
Finish:	Black paint
Grill:	Aluminum with anti-corrosion coat
Dimensions (mm / Inch):	111 W – 98 D – 880 H / 4.4 W – 3.9 D – 34.7 H
Weight:	7.2 kg / 15.9 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk