CS103T

10 × 3" + 6 × 1.2" COLUMN ARRAY SPEAKER



Features

- 10 × 3" column speaker
- Aluminum enclosure
- 10 × 3" woofers, 6 × 1.2" soft dome tweeters
- IP-55 rated waterproof
- Included wall mount
- Both Speakon and EUROBLOCK connectors

Technical Specifications

Feature	Specification
Frequency Response:	100 Hz – 20 kHz
Sensitivity	102 dB, 1W @ 1m
SPL Max:	127 dB (Peak)
Dispersion (H × V):	140° × 25° (H × V)
Loudspeaker Data:	
Configuration:	10 × 3" passive column array speaker
Transducer:	LF: 10 × 3", HF: 6 × 1.2" dome tweeters
Impedance:	8 Ω
Power Handling:	300W / 600W
70v:	120 W / 60 W / 30 W / 15 W
100v:	120 W / 60 W / 30 W
Connectors:	Speakon & EUROBLOCK connectors w/ waterproof cover
Physical:	
Cabinet Construction:	Extrusion aluminum
Mounting:	Wall-mount bracket or pole-mount adapter
Finish:	Black paint
Grill:	Powder-coated marine-grade metal
Dimensions (mm / Inch):	111 W – 98 D – 1323 H / 4.4 W – 3.9 D – 48.5 H
Weight:	10.9 kg / 24 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk