QUA8

8" 2 WAY PREMIUM WALL SPEAKERS



Features

- 8" coaxial surface-mount speaker
- 8" woofer and 1" coaxial compression driver
- Multi-tap transformer 70V/100V
- IP-56 all weather protection for indoor/outdoor
- Included 4-way adjustable bracket

Technical Specifications

Feature	Specification
Frequency Response:	50 Hz – 18 kHz
Sensitivity	99 db
SPl Max:	119 db
Dispersion (H × V):	120° Conical
Loudspeaker Data	
Configuration:	8" coaxial speaker
Transducer:	LF: 8"; HF: 1" coaxial compression driver
Impedance:	8Ω
Power Handling (passive):	100 / 400W
70v:	30 / 15 / 7.5 / 3.75W
100v:	30 / 15 / 7.5W
Connectors:	4 pin euroblock (parallel)
Physical	
Cabinet Construction:	ABS
Mounting:	Yoke mount bracket
Finish:	Matte finish
Grill:	Metal with spray coating
Control:	70V / 100V / 8-ohm tap switch
Dimensions (mm / Inch):	246 W – 315 D – 351 H / 9.7 W – 12.4 D – 13.8 H
Weight:	6 kg / 13.2 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk