CS42Q

4.5" COAXIAL IN-CEILING SPEAKER

Features

- 4.5" coaxial in-ceiling speaker
- 4.5" woofer and a 1" coaxial compression driver
- Multi-tap transformer 70V/100V
- Included bridge rail installation kit
- White-painted magnetic grill coupled with a sturdy steel backcan



Technical Specifications

Feature	Specification
Frequency Response	75 Hz - 20 kHz
Sensitivity	90 dB
SPL Max	108 dB
Dispersion (H x V)	140° Conical
Configuration	4.5" coaxial in-ceiling speaker
Transducer	LF: 4.5", HF: 1" coaxial compression driver
Impedance	8 Ω
Power Handling (passive)	50/100W
70V	8/4/2/1W
100V	16/8/4/2W
Connectors	4 pole euroblock connector
Cabinet Construction	Zinc plated steel
Mounting	Bridge rail installation kit
Finish	White painted
Grill	Powder coated steel grille with safety clip
Control	70V/100V/8-ohm tap switch
Dimensions (mm / Inch)	Φ 213.2 × 142.3 H / Φ 8.4 × 5.6 H
Weight	2.23 kg / 4.9 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk