POINT 46DSP

HIGH-POWER 4 × 6.5" POWERED COLUMN SPEAKER



Features

- Four 6.5" woofers and dual 3/4" compression drivers with linear horns.
- Included U-bracket, 10° adapter and extension plate.
- Optional flying frame.
- Birch plywood enclosure.
- Class D amplifier with DSP.

Technical Specifications

Feature	Specification
Frequency Response:	85 Hz – 20 kHz
Sensitivity:	106 dB
SPL Max:	134 dB
Dispersion (H × V):	120° × 20°
Loudspeaker Data	
Configuration:	4 × 6.5" powered full range column speaker
Transducer:	LF: 4 × 6.5", HF: 2 × 0.75" compression drivers
Impedance:	8 Ω
Power Handling:	600 W / 1200 W
Physical	
Cabinet Construction:	High grade 100% birch plywood
Mounting:	U Bracket + 10° adapter / Optional Flying Frame / 35 mm stand socket
Finish:	Texture coating (RAL colors available)
Grill & Rigging Component:	Powder-coated marine-grade metal
Dimensions (mm / inch):	200 W – 260 D – 932 H / 7.9 W – 10.2 D – 36.7 H
Weight:	19.5 kg / 43 lbs
Amplifier	
Amplifier:	Class D amplifier with DSP
Input:	2 × 1/4" & XLR combo (MIC/LINE) + 1 × 1/8" (AUX) / Bluetooth
Output:	XLR mixed out
Control:	DSP with LCD; 2-channel input gain, rotary push-encoder DSP (EQ, BASS BOOST, DELAY, etc.)
Voltage:	100V–240V (50–60 Hz)

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk