L28DSP

2 × 8" ACTIVE LINEARRAY SPEAKER



Features

- Dual 8" active full range line array speaker.
- 2×8" LF, 2× 3/8" titanium compression drivers.
- Built-in class D amp w/ onboard DSP.
- Perfect for a range of installation applications, such as live performances, clubs, churches, and other venues that demand a high-performance line array speaker system.

Technical Specifications

Feature	Specification
Frequency Response:	60 Hz – 19k Hz
Sensitivity	103 db
Spl Max:	132 db
Dispersion:	90° × 15° (H × V)
Loudspeaker Data	
Configuration:	Dual 8" Powered Line Array Speaker
Transducer:	LF: 2 × 8" woofers, HF: 2 × 1 3/8" titanium compression drivers
Impedance:	4Ω Nominal
Power Handling	800W / 1600W
Connectors:	/
Physical	
Cabinet Construction:	ABS
Mounting:	Compact line array hardware
Finish:	Texture coating
Grill And Rigging Component:	Steel with anti-corrosion coat
Dimensions (mm / Inch):	581 W – 292 D – 434 H / 22.9 W – 11.5 D – 17.1 H
Weight:	19.5 Kg
Amplifier:	Class-D amplifier with DSP
Input:	1/4"&XLR combo
Output:	XLR thru. Out
Control:	DSP: HF, HIGH CURVING, 4 selectable mode
Voltage:	Neutrik PowerCON in & out 100V~240V (50~60Hz)

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk