CS123T

12 × 3" – 8 × 1.2" COLUMN ARRAY SPEAKER



Features

- 12 × 3" woofers, 8 × 1.2" soft dome tweeters
- Stable and consistent 140° × 25° coverage
- Direct-radiating units deliver ultra-wide horizontal dispersion
- Multi-tap transformer 70V/100V
- IP-55 rated waterproof
- Included wall mount bracket
- Barrier strip connectors

Technical Specifications

Feature	Specification
Frequency Response:	95 Hz – 20 kHz
Sensitivity	102 dB, 1W @ 1m
Spl Max:	131 dB (Peak)
Dispersion:	140° × 20° (H × V)
Loudspeaker Data:	
Configuration:	12 × 3" passive column array speaker
Transducer:	LF: 12 × 3", HF: 8 × 1.2" soft dome tweeters
Impedance:	8 Ω
Power Handling:	380W / 760W
70v:	120 W / 60 W / 30 W / 15 W
100v:	120 W / 60 W / 30 W
Connectors:	Barrier strip connectors
Physical:	
Mounting:	Included wall–mount bracket
Finish:	Black paint
Grill:	Aluminum with anti-corrosion coat
Dimensions (mm / Inch):	136.5 W – 180 D – 1090 H / 5.4 W – 7.1 D – 42.9 H
Weight:	11.72 kg / 25.84 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk