D4600T

4 × 600W @ 100V DSP AMPLIFIER

Features

- Stadium, School, Meeting Room, Airport Terminal
- Hotel, Restaurant, Coffee Bar, Shopping Mall etc.



Technical Specifications

Feature	Specification
Model	D4600T
Output Power (100V line)	600W × 4
Output Power (70V line)	600W × 4
Input Sensitivity	0.9–1.1V (0 ± 1dBV)
Input Impedance	20kΩ (balanced), 10kΩ (unbalanced)
Frequency Response	100Hz – 15kHz
Voltage Gain (100V)	40dB
THD + N	<0.1%
S/N Rate	>95dB
Crosstalk	>70dB
Damping Factor	>200
Power Output Circuitry	Switching power, Class-D
Power Supply	AC 110–120V or 220–240V, 50/60Hz
Protections	Short circuit, open circuit, thermal, ultrasonic, RF
Connectors	Input & Output: Euroblock
Controls	Front: AC switch, input level control for each channel Rear: 70V / 100V selector Optional Dante
Indicators	SIGNAL: green LED CLIP: red LED POWER: green LED LED PROTECTION: red LED PRIOR: green / red LED
Dimensions (W×D×H)	483 × 44 × 360 mm (19 × 1.73 × 14.17 inch)
Weight	6.3 kg / 13.9 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk