OHS6IT

6.5" COAXIAL OUTDOOR SPEAKER



Features

- Compact full range 6.5" coaxial speaker
- Customized high performance woofer & compression driver
- Built-in 70V/100V transformer with power tap switch
- Water-resistant polyvinyl board with quality texture coating
- Hydrophobically-treated Grill
- Water proof strip connector
- U-bracket included for installation
- Suitable for outdoor use IP66

Technical Specifications

Feature	Specification
Frequency Response:	80 Hz – 20k Hz
Sensitivity	105 db
Spl Max:	127 db
Dispersion (H × V):	110° × 110°
Loudspeaker Data:	
Configuration:	6.5" Full range coaxial speaker
Transducer:	LF: 1 × 6.5", HF: 1" Compression driver (coaxial)
Impedance:	8Ω Nominal
Power Handling (passive):	150W RMS / 300W Program
70v:	60W / 30W / 15W / 7.5W
100v:	60W / 30W / 15W
Connectors:	Water-proof 4 pin terminal strip connector
Physical:	
Cabinet Construction:	Water-resistant polyvinyl board
Mounting:	U bracket
Finish:	Texture coating
Grill:	Aluminum with anti-corrosion coat
Dimensions (mm / Inch):	256 W – 275 D – 251 H / 10 W – 10.8 D – 10 H
Weight:	9.2 kg / 20 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk