OHS15WIT

15" COAXIAL OUTDOOR SUBWOOFER HORN LOADED SPEAKERS



Features

- Durable plastic cabinet with metal grille
- Power selector switch with 8 ohms operating position
- Screw terminals for parallel connection
- With mounting bracket
- Suitable for outdoor use IP66
- For application areas such as: Installation; sports centres/gyms; multi-purpose hall

Technical Specifications

Feature	Specification
Frequency Response	45 Hz - 300 Hz
Sensitivity	108 dB (1W/1m)
SPL Max	136 dB
Dispersion (H x V)	Omnidirectional
Configuration	Passive subwoofer (vented)
Transducer	1 × 15″ woofer, 3″ voice coil
Impedance	8 Ω nominal; also compatible with 100V line systems
Power Handling (passive)	500W RMS / 1000W Program
70V	N/A
100V	75W / 150W / 300W (selectable via switch)
Connectors	Screw terminal (input)
Dimensions (mm/Inch)	490 W × 520 D × 500 H / 19.3 W × 20.5 D × 19.7 H
Weight	24.8 kg / 54.7 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk