POINT SUB18DSP

18" ACTIVE SUBWOOFER



Features

- 18" LF with 4" voice coil.
- 2.1 Channel with 2 speaker outputs.
- High-grade 100% birch plywood enclosure.
- Class D amplifier with DSP.

Technical Specifications

Feature	Specification
Frequency Response:	38 Hz – 180 Hz
Sensitivity:	99 dB
SPL Max:	132 dB
Dispersion (H × V):	Omnidirectional
Loudspeaker Data	
Configuration:	18" 2.1 channel powered subwoofer
Transducer:	LF: 18" woofer, HF: —
Impedance:	8 Ω
Power Handling:	2000 W @ 2 × 500 W
Physical	
Cabinet Construction:	High-grade 100% birch plywood
Mounting:	M20 stand mount on top
Finish:	Texture coating (RAL colors available)
Grill:	Steel with anti-corrosion coat
Dimensions (mm / inch):	529 W – 550 D – 599 H / 20.8 W – 21.7 D – 23.6 H
Weight:	38.6 kg / 85 lbs
Amplifier:	
Amplifier:	Class D amplifier with DSP
Input:	2 × XLR–1/4" combo (line input)
Output:	2 × XLR (thru line out), 2 × speakon + 2 × binding post (power output)
Control:	Subwoofer: Polarity, volume Satellite: L/R balance, volume, high pass filter
Indicator:	Power, clip
Voltage:	100V–240V (50–60 Hz)

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk