OHS15IT

15" COAXIAL OUTDOOR HORN LOADED SPEAKER



Features

- 2-way coaxial system with 38 cm woofer (15″) and 3.6 cm tweeter (1.4″)
- Durable plastic cabinet with metal grille
- Power selector switch with 8 ohms operating position
- Screw terminals for parallel connection
- With mounting bracket
- Suitable for outdoor use IP66
- For application areas such as: Installation; sports centres/gyms; multi-purpose hall

Technical Specifications

Feature	Specification
Frequency Response	50 Hz - 18000 Hz
Sensitivity	111 dB (1W/1m)
SPL Max	138 dB
Dispersion (H x V)	80° × 80°
Configuration	2-way passive, on-ceiling/on-wall speaker
Transducer	LF - 1 × 15″ woofer (3″ voice coil); HF - 1 × 1.4″ compression driver (3″ voice coil)
Impedance	8 Ω Nominal; public address systems 100V
Power Handling (passive)	1000W RMS / 2000W Program
70V	N/A
100V	75W / 150W / 300W / 400W RMS (selectable via rotary switch)
Connectors	Screw terminal (input)
Dimensions (mm/Inch)	468 W × 595 D × 500 H / 18.4 W × 23.4 D × 19.7 H
Weight	30.55 kg / 67.3 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk