OHS10IT

10" COAXIAL OUTDOOR SPEAKER



Features

- Compact full range 10" coaxial speaker
- Customized high performance woofer & compression driver
- Built-in 70V/100V transformer with power tap switch
- Water-resistant polyvinyl board with quality texture coating
- Hydrophobically-treated Grill
- Water proof strip connector
- U-bracket included for installation

Technical Specifications

Feature	Specification
Frequency Response:	70 Hz – 20k Hz
Sensitivity	109 db
Spl Max:	133 db
Dispersion (H × V):	95° × 95°
Loudspeaker Data:	
Configuration:	10" Full range coaxial speaker
Transducer:	LF: 1 × 10", HF: 1–3/8" Compression driver (coaxial)
Impedance:	8Ω Nominal
Power Handling (passive):	250W RMS / 500W Program
70v:	200W / 100W / 50W / 25W
100v:	200W / 100W / 50W
Connectors:	Water-proof 4 pin terminal strip connector
Physical:	
Cabinet Construction:	Water-resistant polyvinyl board
Mounting:	U bracket
Finish:	Texture coating
Grill:	Aluminum with anti-corrosion coat
Dimensions (mm / Inch):	330 W – 370 D – 330 H / 13 W – 14.6 D – 13 H
Weight:	15.3 kg / 33.7 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk