DS12ADSP

12" ACTIVE DSP 2 WAY SPEAKER



Features

- 12" powered full-range PA speaker
- Customized high-efficient LF & titanium compression driver
- Class-D amplifier with onboard DSP
- Support TWS Bluetooth
- 100% high-grade plywood with quality texture coating

Technical Specifications

Feature	Specification
Frequency Response	50 Hz – 19 kHz
Sensitivity	106 dB
SPL Max	134 dB
Dispersion	90° × 60°
Configuration	12" powered full range
Transducer	LF: 1 × 12″, HF: 1 × 1-3/8″ titanium compression driver
Impedance	8Ω Nominal
Power Handling	700W / 1400W
Cabinet Construction	High-grade 100% birch plywood
Mounting	Metal stand mount on bottom
Finish	Texture coating
Grill & Rigging Component	Steel with anti-corrosion coat
Dimensions (mm / inch)	350 W – 360 D – 600 H / 13.8 W – 14.2 D – 23.6 H
Weight	18.4 kg / 40.5 lbs
Amplifier	Class-D amp with onboard DSP
Input	2-Channel 1/4" & XLR combo, 1/8" AUX, TWS Bluetooth
Output	XLR (mix out)
Control	2-channel input gain, Onboard DSP (Mode, EQ, Bass boost, Delay, etc.)
Indicator	LCD display
Voltage	100–240V, 50/60 Hz

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk