DS15ADSP

15" POWERED FULL RANGE PA SPEAKER



Features

- Customized high efficient LF & titanium compression driver
- Class-D amplifier with onboard DSP
- Support TWS Bluetooth
- 100% high grade plywood with quality texture coating

Technical Specifications

Feature	Specification
Frequency Response	45 Hz – 19 kHz
Sensitivity	106 dB
SPL Max	135 dB
Dispersion (H × V)	90° × 60°
Configuration	15" powered full range
Transducer	LF: 1 × 15″, HF: 1 × 1-3/8″ titanium compression driver
Impedance	8Ω Nominal
Power Handling	800 / 1600W
Cabinet Construction	High grade 100% birch plywood
Mounting	Metal stand mount on bottom
Finish	Texture coating
Grill	Steel with anti-corrosion coat
Dimensions (mm / inch)	420 W – 430 D – 680 H / 16.5 W – 16.9 D – 26.8 H
Weight	23.6 kg / 52 lbs
Amplifier	Class-D amp with onboard DSP
Input	2 Channel 1/4" & XLR combo, 1/8" AUX, TWS Bluetooth
Output	XLR (mix out)
Control	2-channel input gain, Onboard DSP (Mode, EQ, Bass boost, Delay, etc.)
Indicator	LCD display
Voltage	100–240V, 50/60 Hz

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk