QUA 4

4.5” 2 WAY PREMIUM WALL SPEAKERS



Features

- 4.5" coaxial surface-mount speaker
- 4.5" woofer and a 1" coaxial compression driver
- Multi-tap transformer 70V/100V
- IP-56 all weather protection for indoor/outdoor
- Included 4-way adjustable bracket

Technical Specifications

Feature	Specification
Frequency Response	70 Hz – 18K Hz
Sensitivity	96 dB
SPL Max	113 dB
Dispersion (H x V)	120° Conical
Loudspeaker Data	
Configuration	4.5" coaxial speaker
Transducer	LF: 4.5", HF: 1" coaxial compression driver
Impedance	8 Ω
Power Handling (passive)	50 / 100 / 200W
70V Taps	30 / 15 / 7.5 / 3.75W
100V Taps	30 / 15 / 7.5W
Connectors	4 pin euroblock (parallel)
Physical	
Cabinet Construction	ABS
Mounting	Yoke mount bracket
Finish	Matte finish
Grill	Metal with spray coating
Control	70V / 100V / 8-ohm tap switch
Dimensions (mm / inch)	163 W – 165 D – 244 H / 6.4 W – 6.5 D – 9.6 H
Weight	3.4 kg / 7.6 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk