OHS1010SUB

DUAL 10" WEATHER-RESISTANT SUBWOOFER



Features

- Dual Customized high performance woofers
- Water-resistant fiber glass enclosure with quality texture coating
- Hydrophobically-treated aluminum Grill
- Water proof strip connector
- U-bracket included for installation

Technical Specifications

Feature	Specification
Frequency Response:	40Hz – 500Hz
Sensitivity:	105 db
Spl Max:	132 db
Dispersion (H × V):	Omnidirectional
Loudspeaker Data:	
Configuration:	Dual 10" Weather-Resistant Subwoofer
Transducer:	LF: 2 × 10" Woofer, HF: --
Impedance:	4Ω Nominal
Power Handling (passive):	500 / 1000W
Connectors:	4 PIN SPEAKON
Physical:	
Cabinet Construction:	Fiber Glass
Mounting:	U Bracket
Finish:	Texture coating
Grill:	Aluminum with anti-corrosion coat
Dimensions (mm / Inch):	770 W – 320 D – 418 H / 30.3 W – 12.6 D – 16.5 H
Weight:	60.2 lbs / 27.3 kg

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk