OHS1010

DUAL 10" FULL-RANGE WEATHER-RESISTANT COAXIAL LOUDSPEAKER



Features

- Customized high performance woofers & compression driver
- Water-resistant fiber glass enclosure with quality texture coating
- Hydrophobically-treated aluminum Grill
- Water proof strip connector
- U-bracket included for installation

Technical Specifications

Feature	Specification
Frequency Response:	52Hz – 19kHz
Sensitivity:	110 db
Spl Max:	137 db
Dispersion (H × V):	120° × 60°
Loudspeaker Data:	
Configuration:	Dual 10" full-range coaxial loudspeaker
Transducer:	LF: 2 × 10" woofer, HF: 1.75" compression driver
Impedance:	8Ω Nominal
Power Handling (passive):	500/1000W
Connectors:	2 × 4-pin Speakon
Physical:	
Cabinet Construction:	Fiber Glass
Mounting:	U Bracket
Finish:	Texture coating
Grill:	Aluminum with anti-corrosion coat
Dimensions (mm / Inch):	770 W – 320 D – 418 H / 30.3 W – 12.6 D – 16.5 H
Weight:	65.0 lbs / 29.5 kg

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk