CS51 EN

EN54-24 5"CEILING SPEAKER

Features

The LUCASACS CS51EN, EN54-24 5” Ceiling Speaker ,one quick mount ceiling speaker, 5" 6W/3W with 100V transformer, ideal for background music system and PA system use.



- Compliant with the EN54-24 standards
- Built-in 100v/70v transformer for PA & VA system
- Commercial fireproof ceiling speaker with transformer
- Ceramic connector, fire dome, 95? fire-resistant cable and thermal fuse.
- Rated power output 6 /3 /1.5 /0.75 W at 100V
- 5' dual cone fire resistant finish and rustproof speaker unit
- V0 fire resistant ABS enclosure,back box and metal grille in white

EN54 Certified

Technical Specifications

Description	EN54-24 5” Ceiling Speaker
Power Taps 100V	0.75W-1.5W-3W-6W
Sensitivity 1W/1m	92±2dB and Max 98±2dB
Frequency Response	105Hz-15KHz
Speaker Driver	5” dual cone fire resistant finish and rustproof speaker unit
Finish	V0 fire resistant ABS enclosure,back box and metal grille in white
Mounting Way	In-ceiling spring clip quick installation
Cutout Size	Ø140mm
Dimensions	Ø165×89mm
Weight	0.6kg

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk