LX5T

5" COAXIAL COLUMNARRAY SPEAKER



Features

- Ultra compact 5" coaxial passive full range speaker cube.
- 5" LF, 1" HF coaxial design, point source to improve radiation output.
- High-grade plywood with quality texture coating available in black and white.
- Installation U bracket included in package.
- Used in meeting rooms, multi-function halls, lounge bars, schools, churches, restaurants and broadcasting media.

Technical Specifications

Feature	Specification
Frequency Response:	95 Hz – 18 kHz
Sensitivity:	105 dB
SPL Max:	125 dB
Dispersion (H × V):	120° conical
Loudspeaker Data:	
Configuration:	5" ultra compact coaxial cubes
Transducer:	LF: 1 × 5", HF: 1 × 1" diaphragm coaxial
Impedance:	8? Nominal
Power Handling:	8 ohm: 100–200–400 W; 100V: 60/30/15 W
Connectors:	4 Pin Euroblock
Physical	
Cabinet Construction:	High grade 100% birch plywood
Mounting:	U bracket
Finish:	Texture coating (RAL colors available)
Grill:	Steel with anti-corrosion coat
Dimensions (mm / inch):	190 W – 190 D – 190 H / 7.5 W – 7.5 D – 7.5 H
Weight:	4 kg / 8.8 lbs

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk