DSSUB15ADSP

15" POWERED SUBWOOFER



Features

- Customized high-power LF with 4" voice coil
- Class-D amplifier with DSP, Xover, Mode switch
- 100% high-grade plywood with quality texture coating

Technical Specifications

Feature	Specification
Frequency Response	35 Hz – 180 Hz
Sensitivity	104 dB
SPL Max	133 dB
Dispersion (H × V)	Omnidirectional
Configuration	15" powered subwoofer
Transducer	LF: 1 × 15"
Impedance	8Ω Nominal
Power Handling	800 / 1600W
Cabinet Construction	High-grade 100% birch plywood
Mounting	Metal stand mount on top
Finish	Texture coating
Grill	Steel with anti-corrosion coat
Dimensions (mm / inch)	430 W – 460 D – 510 H / 16.9" W – 18.1" D – 20" H
Weight	28.1 kg / 62 lbs
Amplifier	Class-D with DSP
Input	2 × 1/4" & XLR combo
Output	2 × XLR
Control	Volume, Polarity, Xover, Output Mode
Indicator	Power, Limit, Signal
Voltage	100–240V, 50/60 Hz

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk