DSSUB18ADSP

18" ACTIVE DSP SUBWOOFER



Features

- 18" powered subwoofer
- Customized high-power LF with 4" voice coil
- Class-D amplifier with DSP, Xover, Mode switch
- 100% high-grade plywood with quality texture coating

Technical Specifications

Feature	Specification
Frequency Response:	30 Hz – 180 Hz
Sensitivity	104 db
Spl Max:	134 db
Dispersion:	Omnidirectional
Loudspeaker Data	
Configuration:	18" powered subwoofer
Transducer:	LF: 1 x 18"
Impedance:	8Ω Nominal
Power Handling	1000W / 2000W
Physical	
Cabinet Construction:	High grade 100% birch plywood
Mounting:	Metal stand mount on top
Finish:	Texture coating
Grill And Rigging Component:	Steel with anti–corrosion coat
Dimensions (mm / Inch):	530 W – 550 D – 600 H / 20,8 W – 21,6 D – 23,6 H
Weight:	36,3 kg / 80 lbs
Amplifier:	Class–D with DSP
Input:	2 x 1/4" & XLR combo
Output:	2 x XLR
Control:	Volume, Polarity, Xover, Output mode
Indicator:	Power, Limit, Signal
Voltage:	100~240V, 50/60 Hz

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk