LX108

SINGLE 8" PASSIVE FULL RANGE SPEAKER



Features

- 8" LF with 2" voice coil, 1.4" titanium compression driver.
- High grade plywood with quality texture coating available in black and white.
- U bracket included for installation.
- Used in meeting rooms, multi-function halls, bars, museums, churches, KTV etc.

Technical Specifications

Feature	Specification
Frequency Response:	65 Hz – 20 kHz
Sensitivity:	96 dB
SPL Max:	128 dB
Dispersion (H × V):	100° × 55° (Horn rotatable)
Loudspeaker Data	
Configuration:	8" multi-angle full range loudspeaker
Transducer:	LF: 1 × 8", HF: 1 × 1.4" diaphragm
Impedance:	8Ω Nominal
Power Handling:	350 / 700 W
Connectors:	2 × 4 Pin Speakon®, Barrier Strip
Physical	
Cabinet Construction:	High grade 100% birch plywood
Mounting:	M8 inserts / U bracket
Finish:	Texture coating (RAL colors available)
Grill & Rigging Component:	Steel with anti-corrosion coat
Dimensions (mm / inch):	250 W – 230 D – 445 H / 9.8 W – 9.1 D – 17.5 H
Weight:	9 kg / 19.8 lb

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk