DSMN10DSP

10" COMPACT 2-WAY ACTIVE MONITOR

Features

- Customized 10″ coaxial speaker
- Class-D amplifier with DSP
- Optional U-bracket for installation
- High-grade plywood with quality texture coating (black & white available)
- Ideal for meeting rooms, multi-function halls, bars, museums, churches, KTV, etc.



Technical Specifications

Feature	Specification
Frequency Response	52 Hz – 20 kHz
Sensitivity	98 dB
SPL Max	123 dB
Dispersion	100° conical
Configuration	10″ compact 2-way active monitor
Transducer	LF: 1 × 10″, HF: 1″ coaxial compression driver
Impedance	8Ω Nominal
Power Handling	300 / 600W
Cabinet Construction	High-grade 100% birch plywood
Mounting	Optional U-bracket
Finish	Texture coating (RAL colors available)
Grill & Rigging Component	Steel with anti-corrosion coat
Dimensions (mm / inch)	400 W × 281 D × 305 H / 15.7″ W × 11.1″ D × 12″ H
Weight	11.5 kg / 25.4 lb
Amplifier	Class-D amplifier with DSP
Input	1/4″ & XLR (Mic/Line), 1/8″ Aux
Output	XLR Line out
Control	Volume, EQ, Gain
Indicator	Power, Limit
Voltage	100V–240V (50–60 Hz)

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk