WSB51 EN

EN54-24 5" WALL MOUNT SPEAKER

Features

The LUCASACS WSB51EN , EN54-24 certified wall mount speaker with fire dome, all metal, ceramic connector, thermal fuse and dedicated designed for voice alarm & voice evacuation system use.



- Compliant with the EN54-24 standards
- Commercial fireproof wall mount speaker with 100V/70V transformer
- Ideal for school, office, hotel and airport voice evacuation and PA system
- Rated power output 1.5W-3W-6W at 100V
- 5' full range driver unit
- Line input 100V or 70V with transformer
- Ceramic connector, fire dome, 95? fire-resistant cable and thermal fuse
- Steel enclosure, steel grille and fire dome in white
- Wall mount or surface mount quick installation by screw hole

EN54 Certified

Technical Specifications

Description	EN54-24 Wall Mount Speaker
Rated Power Output	1.5W-3W-6W
Line Input	100V or 70V
Frequency Response	120-10KHz
SPL(@1W/m)	92dB/Max 99dB
Speaker Unit	5" full range driver unit
Dimension	165×165×60mm
Material	Steel enclosure, steel grille and fire dome in white
Mounting Way	Quick installation by hanging screw hole
Weight	1.4kg

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk