QLASUB15DSP

15" ACTIVE LINE ARRAY SUBWOOFER

Features

- 15" customized high power LF with 4" voice coil.
- High grade plywood with quality texture coating available in black and white.
- Used in small and mid-size live sound venues, permanent installation in clubs, ballrooms, restaurants, houses of worship, convention centres, live theatres etc.
- Class D amplifier with DSP



Technical Specifications

Feature	Specification
Frequency Response:	38 Hz – 180 Hz
Sensitivity:	104 db
Spl Max:	133 db
Dispersion:	Omnidirectional
Loudspeaker Data:	
Configuration:	15" active line array subwoofer
Transducer:	LF: 1 × 15"
Impedance:	8Ω Nominal
Power Handling:	800 / 1600W
Physical:	
Cabinet Construction:	High grade 100% birch plywood
Mounting:	Integrated line array hardware
Finish:	Texture coating (RAL colors available)
Grill And Rigging Component:	Steel with anti-corrosion coat
Dimensions (mm / Inch):	671 W – 621 D – 450 H / 26.4 W – 24.4 D – 17.7 H
Weight:	42.5 kg / 93.7 lbs
Amplifier:	
Amplifier:	CLASS D amplifier with DSP
Input:	2 × 1/4" & XLR combo
Output:	2 × XLR (Full Range / High Pass)
Control:	Volume, polarity, LPF
Voltage:	Neutrik PowerCON in & out 100V–240V (50~60Hz)

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk