QLA210DSP

DUAL 10" ACTIVE FULL RANGE LINE ARRAY SPEAKER



Features

- 2×10" LF, 2 × 1.4" titanium compression driver,
- Passive model Bi-amp / Full range switchable,
- Active model built-in Class D amp. w/ onboard DSP
- High grade plywood with quality texture coating available in black and white.
- Fit with QLASUB18DSP/QLASUB218DSP subwoofer.
- Used in small and mid-size live sound venues, permanent installation in clubs, ballrooms, restaurants, houses of worship, convention centres, live theatres etc.

Technical Specifications

Feature	Specification
Frequency Response:	52 Hz – 19k Hz
Sensitivity	107 db
Spl Max:	135 db
Dispersion:	120° × 15° (H × V)
Loudspeaker Data:	
Configuration:	Compact dual 10" active full range line array
Transducer:	LF: 2 × 10", HF: 2 × 1.4" diaphragm
Impedance:	4Ω
Power Handling	1200 / 2400W
Connectors:	2 × 4 Pin Speakon®
Physical:	
Cabinet Construction:	High grade 100% birch plywood
Mounting:	Compact line array hardware
Finish:	Texture coating (RAL colours available)
Grill And Rigging Component:	Steel with anti-corrosion coat
Dimensions (mm / Inch):	796 W – 420 D – 320 H / 30.3 W – 16.5 D – 12.6 H
Weight:	31.5 kg / 69 lbs
Amplifier:	Class-D amp. with DSP
Input:	2 × 1/4" & XLR combo, 1/8" Aux
Output:	2 × XLR line out
Control:	Volume, onboard DSP
Voltage:	Neutrik PowerCON in & out 100V~240V (50~60Hz)

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk