LX12ADSP

12" ACTIVE DSP SUBWOOFER



Features

- 12" compact active subwoofer with Class-D amplifier.
- 1 × 12" LF with 3" voice coil.
- High grade plywood with quality texture coating available in black and white.
- Used in meeting room, multi-function hall, bar, museum, church, KTV etc. for bass reinforcement.

Technical Specifications

Feature	Specification
Frequency Response:	40 Hz – 180 Hz
Sensitivity:	103 db
Spl Max:	130 db
Dispersion:	Omnidirectional
Loudspeaker Data:	
Configuration:	12" active subwoofer
Transducer:	LF: 1 × 12"
Impedance:	8Ω Nominal
Power Handling:	500 / 1000W
Physical:	
Cabinet Construction:	High grade 100% birch plywood
Mounting:	Stand mount on top
Finish:	Texture coating (RAL colors available)
Grill And Rigging Component:	Steel with anti-corrosion coat
Dimensions (mm / Inch):	360 W – 450 D – 650 H / 14.2 W – 17.7 D – 25.6 H
Weight:	29 kg / 63.9 lb
Amplifier:	
Amplifier:	CLASS D
Input:	2 × 1/4" & XLR combo, RCA Line in
Output:	2 × XLR Line out
Control:	Volume, Polarity, LPF
Indicator:	Power, Clip
Voltage:	100V–240V (50~60Hz)

71 - 75 Shelton Street Covent Garden WC2H 9JQ LONDON U.K.
+44 204 577 07 66
info@lucasacs.co.uk